

Engine	Cummins QSB4.5
Gross Power	97 kW (132 hp)
Net Power	89.5 kW (122 hp)
Maximum Digging Depth	4,912 mm
Standard Bucket Capacity	0.58 m ³
Operating Weight	14,600 kg

W915E

WHEEL EXCAVATOR



TOUGH WORLD. TOUGH EQUIPMENT.

W915E SPECIFICATIONS >>>

ENGINE

Emission Regulation	Tier 3 / Stage IIIA
Make	Cummins
Model	QSB 4.5
Gross Power	97 kW (132 hp) @ 2,200 rpm
Net Power	89.5 kW (122 hp) @ 2,200 rpm
Peak Torque	620 N·m @ 1,500 rpm
Number of Cylinders	4
Displacement	4.5 L

UNDERCARRIAGE

Maximum Travel Speed, fwd	30 km/h
Maximum Travel Speed, rev	30 km/h
Drawbar Pull	90 kN
Front Axle Oscillation	±7°
Turn Angle	35°
Turning Radius	7,000 mm
Tire Size	10.00-20
Wheel Base	2,800 mm
Wheel Track	1,944 mm

HYDRAULIC SYSTEM

Main Pumps Total Flow	2 × 153 L/min
Relief Pressure, main	34.3 MPa
Relief Pressure, boost	37.3 MPa

SWING SYSTEM

Swing Speed	12.9 rpm
-------------	----------

REFERENCE ARM

Arm Length	2,100 mm
Arm Breakout Force, max, ISO	73.9 kN

WORKING RANGES

Maximum Dig Depth	4,912 mm
Maximum Reach	7,981 mm
Reach at Ground Level	7,786 mm
Depth of 8' Level Bottom	4,665 mm
Maximum Dig Height	8,830 mm
Dump Height	6,346 mm
Maximum Dig Depth of Vertical Wall	4,324 mm

BUCKET PERFORMANCE

Standard Bucket Heaped Capacity (Referenced)	0.58 m ³
Minimum Heaped Capacity of Bucket Options	0.58 m ³
Maximum Heaped Capacity of Bucket Options	0.58 m ³
Bucket Breakout Force, max, ISO	92.8 kN

SERVICE CAPACITIES

Fuel Tank	260 L
Engine Oil	14 L
Cooling System	21 L
Hydraulic Reservoir	120 L
Hydraulic System Total	200 L

